

Driver : _____
 Date : _____
 Track : _____
 Event : _____

Track Condition
 Size : Open ☐ Med. ☐ Tight ☐
 Traction : High ☐ Med. ☐ Low ☐
 Condition : Smooth ☐ Bumpy ☐ Dry ☐ Wet ☐
 Dusty ☐ Grooved ☐ Hard Packed ☐

Front Suspension

Shock Tower
 Alu. ☐ CFRP ☐

Upper: Alu. ☐ Steel ☐
Lower: Alu. ☐ Steel ☐

Upper Ball Spacer mm

Front Link Mount 1 2 3 4 5 6 7 8 9 ☐

Front Arm Mount F ☐

Front Arm Mount R ☐

Caster Spacer mm

Ball Position: Forward ☐ Back ☐

Lower Arm Spacer mm

Lower Arm Plate

Lower Arm Type
 STD. ☐ LW. ☐

Upper: Alu. ☐ Steel ☐
Lower: Alu. ☐ Steel ☐

Bump Spacer mm

Wheel Hex

Upright Type
 0 ☐ 1.5 ☐

Ride Height : _____ **Toe :** _____

Anti-Roll Bar :

F Upright Arm : 0 Dot ☐ 1 Dot ☐

Drive Shaft : CVA ☐ Universal ☐

Chassis Brace : Short ☐ Long ☐

Servo Saver Arm : STD. ☐ Alu. ☐

Servo Horn : STD. ☐ Alu. ☐

Size : _____

Rear Suspension

Shock Tower
 Alu. ☐ CFRP ☐

Rear Arm Mount F 1 2 3 4 5 6 ☐

Rear Arm Mount R 1 2 3 4 5 6 7 8 9 ☐

Lower Arm Spacer mm

Lower Arm Type
 STD. ☐ LW. ☐

Hub Spacer mm

Link Spacer mm

Lower Arm Plate

Ball Position: Forward ☐ Back ☐

Wheel Hex

Ride Height : _____ **Camber :** _____

Rear Hub : Plastic ☐ Alu. ☐

Anti-Roll Bar :

Drive Shaft : CVA ☐ Universal ☐

Rear Link Plate : 1Dot ☐ 3Dot ☐

Dot Orientation : In ☐ Out ☐

Shocks	Front	Rear	Differential	Front	Center	Rear
Piston _____ Oil _____ Spring _____ Bladder _____ Emulsion _____ Length _____ Notes : _____			42T/12T ☐ Oil ☐			
			44T/13T ☐ Center ☐	Dog Born ☐		Dog Born ☐
			Drive Shaft ☐	Universal ☐		Universal ☐
			Clutch & Gearing	Spur Gear ☐	T ☐	Bell ☐
			Spring Position: Dot ☐ Non Dot ☐	3Pin ☐	4Shoe ☐	
			Shoe : _____			
			Spring : _____			

Engine	Body & Wing	Tire	Front	Rear
Type	Body	Type		
Muffler	Wing	Compound		
Manifold	Front Wing	Inserts		
Fuel	Gap to Tower	Wheel		
Reducer	1 ☐ 2 ☐ 3 ☐ 4 ☐	Chassis Weight Front : _____ g Rear : _____ g		
Grow Plug		Notes		
Engine Mount : STD. ☐ 1pcs. ☐				